

3M™ Undercoating
08881/60-4400-9649-7

- Multi-purpose coating
- Protects from corrosion & abrasion
- For use on undercarriages, wheel wells and fenders
- Non-chlorinated formula

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. CAUSES EYE IRRITATION.

Read carefully other cautions on the side/back panel.

Multi-purpose, low cost, rubberized aerosol undercoating. Specifically used for undercarriages, wheel wells, frame rails, and fenders. Designed to protect metal from corrosion and abrasion and can also be used as a sound dampening coating for door skins. If painting is required, use Part No. 08882, 3M™ Underseal™ Undercoating 40 or Part No. 08964, 3M™ No Cleanup High Coverage Body Schutz.

DANGER! Extremely flammable liquid and vapor. Vapors may cause flash fire. Contents under pressure. Causes eye irritation. May cause skin, nose and throat irritation and may affect the brain or nervous system causing dizziness, headache or nausea. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Contains chemicals which can cause cancer and birth defects or other reproductive harm.

Directions for Use:

Coating should not be applied to engine, exhaust system or transmission housing.

1. Remove all rust scale, oil, and grease from surface to be coated. Surfaces should be clean and dry.
2. SHAKE WELL until agitator ball moves freely.
3. Spray uniform coats at a distance of 10-12 inches from the surface.
4. Painting over this product is not recommended. (See note.) If painting is required, use Part No. 08883, 3M™ Underseal Rubberized Undercoating or Part No. 08964, 3M™ No Cleanup High Coverage Body Schutz.

Note: Use only in well-ventilated areas. If Undercoating is to be painted, flexibilized automotive enamels or lacquers should be used. Because of the variety of paints, recommended applications techniques, and application procedures, it may not be possible to paint this product to match existing auto finish. If checking, bleed-through, or cracking occurs, it is not considered a deficiency of this product, and 3M assumes no liability for defects or imperfections in the paint surface.

CONTAINS: Calcium Carbonate (471-34-1), Asphalt (8052-42-4), Toluene (108-88-3), Propane (74-98-6), Mineral Spirits (64742-88-7), Butane (106-97-8)

VOC REGULATED MATERIAL: VOC equal to or less than 39.1% (428 g/l • 3.57 lb/gal). Please consult State and Local Regulations.

PRECAUTIONS: Vapors may ignite explosively. Keep away from heat, sparks, open flame, pilot light and other sources of static discharge. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not smoke when using this product. Use only with adequate ventilation. Prevent vapor build-up by opening doors and windows. Ensure fresh air entry during application and drying. Exposure to heat or prolonged exposure to sun may cause bursting. Do not puncture or incinerate (burn) container. Store at temperatures below 120°F (49°C). Avoid eye and skin contact. Avoid breathing vapors, mist or spray. Wash thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

SUGGESTED FIRST AID: **Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes. Get immediate medical attention. **Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse. **Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention. **If Swallowed:** Do not induce vomiting. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get immediate medical attention.

Note to Physicians: Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

Warranty and Limited Remedy: This product will be free from defects in material and workmanship at the time of shipment. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If this product is defective, your exclusive remedy and 3M's and seller's sole obligation shall be, at 3M's option, to replace the product or refund the purchase price.

Additional Product Safety and Health Information Source:

Material Safety Data Sheet (MSDS 19-8684-3) or

3M Automotive Aftermarket Division

3M Center/Bldg. 223-6N-01

St. Paul, MN 55144-1000

1-877-MMM-CARS (666-2277) or 651-737-6501

www.3M.com/automotive

3M is a trademark of 3M Company. © 3M 2005